



Type	Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing intervals [mm]	Connections distance from the wall [mm]	Brackets spacing intervals [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power (75/65/20 °C) [W]	Power (75/65/24 °C) [W]	Power (55/45/24 °C) [W]	Electric heater maximal power [W]
	W	H	D	C	B	A							
LM-508	544	773	100-105	495	52-57	488	0,652	7,6	2,8	339	306	152	300
LMX-508	544	773	100-105	50	77-82	488	0,652	7,8	2,8	339	306	152	300
LM-510	544	1043	100-105	495	52-57	488	0,946	10,9	3,9	483	435	214	300
LMX-510	544	1043	100-105	50	77-82	488	0,946	11,1	3,9	483	435	214	300
LM-513	544	1313	100-105	495	52-57	488	1,241	14,3	5,1	620	559	274	600
LMX-513	544	1313	100-105	50	77-82	488	1,241	14,5	5,1	620	559	274	600



Horizontal tubes:

Vertical manifolds:



Finishing and warranty:

- standard: phosphatizing + polyester-epoxy lacquer; 5 year warranty;
- on request: electrophoresis + polyester-epoxy lacquer; 10 year warranty;

Mounting brackets:

brackets in the same colour as the radiator are included

Valve:

to place a separate order – page 31

Heater:

to place a separate order – page 32

Accessories:

to place a separate order – page 33

Working pressure:

8 bars

Maximal temperature:

95 °C

Connections:



- inner threads G 1/2
- air-vent plug G1/8 hidden behind the radiator

LMX

