

Modello	n elementi	Dimensioni in mm				ø attacchi	Peso a vuoto Kg circa	Contenuto acqua in litri	Potenze termiche EN 442 in Watt		Esponente n	Coefficiente Km
		A	B	C	D				ΔT 50°C	ΔT 30°C		
		altezza totale	lunghezza	profondità	interasse							
SEBINO 350	6	384	500	60	350	1/2"	4,97	0,6	392	201	1,31213	2,316
	8	384	660	60	350	1/2"	6,60	0,8	523	268	1,31213	3,088
	10	384	820	60	350	1/2"	8,26	1,0	654	335	1,31213	3,860
	12	384	980	60	350	1/2"	9,93	1,2	785	402	1,31213	4,632
	14	384	1140	60	350	1/2"	11,63	1,4	916	469	1,31213	5,404
SEBINO 500	6	534	500	60	500	1/2"	6,46	1,2	518	265	1,31417	3,030
	8	534	660	60	500	1/2"	8,58	1,6	690	353	1,31417	4,040
	10	534	820	60	500	1/2"	10,70	2,0	863	441	1,31417	5,050
	12	534	980	60	500	1/2"	12,92	2,4	1036	529	1,31417	6,060
	14	534	1140	60	500	1/2"	15,14	2,7	1208	617	1,31417	7,070
SEBINO 600	6	634	500	60	600	1/2"	7,46	1,2	597	305	1,31553	3,474
	8	634	660	60	600	1/2"	9,91	1,7	796	406	1,31553	4,632
	10	634	820	60	600	1/2"	12,39	2,1	995	508	1,31553	5,790
	12	634	980	60	600	1/2"	14,92	2,5	1194	610	1,31553	6,948
	14	634	1140	60	600	1/2"	17,48	2,9	1393	711	1,31553	8,106
SEBINO 700	6	734	500	60	700	1/2"	8,45	1,3	674	344	1,31688	3,900
	8	734	660	60	700	1/2"	11,23	1,7	898	458	1,31688	5,200
	10	734	820	60	700	1/2"	14,05	2,2	1123	573	1,31688	6,500
	12	734	980	60	700	1/2"	16,91	2,6	1348	688	1,31688	7,800
	14	734	1140	60	700	1/2"	19,82	3,1	1572	802	1,31688	9,100
SEBINO 800	6	834	500	60	800	1/2"	9,45	1,4	748	382	1,31824	4,310
	8	834	660	60	800	1/2"	12,55	1,8	998	509	1,31824	5,744
	10	834	820	60	800	1/2"	15,70	2,3	1247	636	1,31824	7,180
	12	834	980	60	800	1/2"	18,91	2,7	1496	763	1,31824	8,616
	14	834	1140	60	800	1/2"	22,16	3,2	1746	890	1,31824	10,052
SEBINO 900	6	934	500	60	900	1/2"	10,44	1,4	821	418	1,31960	4,700
	8	934	660	60	900	1/2"	13,87	1,9	1094	558	1,31960	6,267
	10	934	820	60	900	1/2"	17,36	2,4	1368	697	1,31960	7,834
	12	934	980	60	900	1/2"	20,90	2,9	1642	836	1,31960	9,401
	14	934	1140	60	900	1/2"	24,50	3,4	1915	976	1,31960	10,968
SEBINO 1000	6	1034	500	60	1000	1/2"	11,44	1,9	890	454	1,32204	5,054
	8	1034	660	60	1000	1/2"	15,20	2,6	1187	605	1,32204	6,738
	10	1034	820	60	1000	1/2"	19,01	3,2	1484	756	1,32204	8,423
	12	1034	980	60	1000	1/2"	22,89	3,8	1781	907	1,32204	10,108
	14	1034	1140	60	1000	1/2"	26,84	4,5	2078	1058	1,32204	11,792
SEBINO 1200	4	1234	340	60	1200	1/2"	9,09	1,4	684	347	1,32691	3,806
	6	1234	500	60	1200	1/2"	13,43	2,1	1025	521	1,32691	5,710
	8	1234	660	60	1200	1/2"	17,84	2,7	1367	694	1,32691	7,613
	10	1234	820	60	1200	1/2"	22,33	3,4	1709	868	1,32691	9,516
SEBINO 1400	4	1434	340	60	1400	1/2"	10,44	1,5	769	390	1,33179	4,202
	6	1434	500	60	1400	1/2"	15,42	2,2	1154	584	1,33179	6,303
	8	1434	660	60	1400	1/2"	20,49	2,9	1538	779	1,33179	8,404
	10	1434	820	60	1400	1/2"	25,64	3,6	1923	974	1,33179	10,505
SEBINO 1600	4	1634	340	60	1600	1/2"	11,79	1,5	851	429	1,34089	4,486
	6	1634	500	60	1600	1/2"	17,41	2,3	1277	644	1,34089	6,729
	8	1634	660	60	1600	1/2"	23,13	3,1	1702	858	1,34089	8,972
	10	1634	820	60	1600	1/2"	28,95	3,9	2128	1073	1,34089	11,215
SEBINO 1800	4	1834	340	60	1800	1/2"	13,14	1,6	929	466	1,34999	4,727
	6	1834	500	60	1800	1/2"	19,40	2,4	1394	700	1,34999	7,090
	8	1834	660	60	1800	1/2"	25,78	3,3	1858	933	1,34999	9,454
	10	1834	820	60	1800	1/2"	32,26	4,1	2323	1166	1,34999	11,817
SEBINO 2000	4	2034	340	60	2000	1/2"	14,49	1,7	1004	502	1,35909	4,929
	6	2034	500	60	2000	1/2"	21,39	2,6	1507	752	1,35909	7,394
	8	2034	660	60	2000	1/2"	28,42	3,4	2009	1003	1,35909	9,858
	10	2034	820	60	2000	1/2"	35,57	4,3	2511	1254	1,35909	12,323

1 Watt = 0,863 Kcal/h



La potenza termica dei radiatori GLOBAL è quella risultante dalle prove effettuate secondo la Norma EN 442.