

IMPORTANT PRODUCT INFORMATION

AVAILABILITY

Standard size radiators are available in colour RAL 9016

Standard size radiator delivery time is 14 working days.

Non-standard size radiators available on request with an eight-week delivery time. Delivery time for radiators in other colours than RAL 9016 can be extended by 14 working days. Please note that for other colours than RAL 9016, there is an additional fee of PLN 250 (excluding VAT) applicable to all colours from Enix colour palette

Double colour finish panel radiators are not available in silver metallic, bronze metallic, chrome effect.

RAL colour palette radiators available upon individual quotation and after delivery time confirmation.

EQUIPMENT

Radiators PLAIN, PLAIN ART – equipped with I-console assembly kit (2 brackets up to 1600mm, 3 brackets up to 1800mm).

8 inches/200mm high units are equipped with Monclac brackets.

The radiator comes with an integrated valve set, thermostatic insert Heimeier 4360 or 4361 (without radiator thermostat) with protective caps and air vent.

Bottom Inlet/outlet with integrated thermostatic valves.

Radiators PLAIN VERTICAL, PLAIN ART VERTICAL are equipped with a Monclac bracket set.

Inlets/outlets located at the bottom/top of the radiator.

APPLICATION

Panel radiators are should be used in closed circuit heating system.

It is possible though to use the radiators in open circuit heating systems equipped with corrosion inhibitors (open loop systems as per PN-91/B-02413 safety standards)

Avoid humid environments (such as swimming pools, saunas, thermal baths, greenhouses and bathrooms).

PLAIN VERTICAL

height →	1600							
	typ 11		typ 20		typ 21		typ 22	
length ↓								
300	588 W 475 W 302 W		693 W 564 W 362 W		842 W 681 W 432 W		1026 W 828 W 522 W	
400	784 W 634 W 402 W		924 W 752 W 483 W		1123 W 908 W 576 W		1368 W 1103 W 696 W	
500	980 W 792 W 503 W		1155 W 940 W 604 W		1404 W 1135 W 720 W		1710 W 1379 W 870 W	
600	1175 W 951 W 603 W		1386 W 1127 W 724 W		1685 W 1362 W 864 W		2052 W 1655 W 1044 W	
700	1371 W 1109 W 704 W		1617 W 1315 W 845 W		1963 W 1589 W 1008 W		2394 W 1931 W 1218 W	

PLAIN ART VERTICAL

height →	1600							
	typ 11		typ 20		typ 21		typ 22	
length ↓								
300	588 W 475 W 302 W		693 W 564 W 362 W		842 W 681 W 432 W		1026 W 828 W 522 W	
400	784 W 634 W 402 W		924 W 752 W 483 W		1123 W 908 W 576 W		1368 W 1103 W 696 W	
500	980 W 792 W 503 W		1155 W 940 W 604 W		1404 W 1135 W 720 W		1710 W 1379 W 870 W	
600	1175 W 951 W 603 W		1386 W 1127 W 724 W		1685 W 1362 W 864 W		2052 W 1655 W 1044 W	
700	1371 W 1109 W 704 W		1617 W 1315 W 845 W		1966 W 1589 W 1008 W		2394 W 1931 W 1218 W	



P max=10 BAR

PLAIN VERTICAL

Energy Efficiency Standards
Table as per PN EN 442

EN442 75/65/20°C

EN442 70/55/20°C

EN442 55/45/20°C

1800								2000								2200								height
typ 11		typ 20		typ 21		typ 22		typ 11		typ 20		typ 21		typ 22		typ 11		typ 20		typ 21		typ 22		length ↓
640 W 518 W 329 W		760 W 618 W 397 W		918 W 743 W 472 W		1107 W 893 W 563 W		689 W 558 W 355 W		824 W 670 W 430 W		981 W 794 W 505 W		1188 W 957 W 603 W		736 W 597 W 380 W		887 W 722 W 463 W		1053 W 853 W 534 W		1269 W 1022 W 634 W		
853 W 691 W 439 W		1013 W 824 W 529 W		1224 W 990 W 629 W		1476 W 1190 W 750 W		919 W 745 W 474 W		1099 W 894 W 574 W		1308 W 1059 W 673 W		1584 W 1277 W 804 W		982 W 796 W 507 W		1183 W 962 W 618 W		1404 W 1137 W 724 W		1692 W 1363 W 858 W		400
1067 W 863 W 549 W		1266 W 1030 W 661 W		1530 W 1238 W 786 W		1845 W 1488 W 938 W		1149 W 931 W 592 W		1374 W 1117 W 717 W		1635 W 1323 W 841 W		1980 W 1596 W 1005 W		1227 W 994 W 634 W		1479 W 1203 W 772 W		1755 W 1421 W 905 W		2115 W 1704 W 1072 W		500
1280 W 1036 W 658 W		1519 W 1236 W 794 W		1836 W 1485 W 943 W		2214 W 1785 W 1125 W		1379 W 1117 W 711 W		1649 W 1341 W 861 W		1962 W 1588 W 1010 W		2376 W 1915 W 1206 W		1472 W 1193 W 761 W		1775 W 1443 W 926 W		2106 W 1706 W 1086 W		2538 W 2045 W 1286 W		600
1493 W 1209 W 768 W		1772 W 1442 W 926 W		2142 W 1733 W 1110 W		2583 W 2083 W 1313 W		1609 W 1303 W 829 W		1924 W 1564 W 1004 W		2289 W 1853 W 1178 W		2772 W 2234 W 1407 W		1718 W 1392 W 887 W		2071 W 1684 W 1081 W		2457 W 1990 W 1267 W		2961 W 2385 W 1501 W		700



P max=10 BAR

PLAIN ART VERTICAL

1800								2000								2200								height
typ 11		typ 20		typ 21		typ 22		typ 11		typ 20		typ 21		typ 22		typ 11		typ 20		typ 21		typ 22		length
640 W 518 W 329 W		760 W 618 W 397 W		918 W 743 W 472 W		1107 W 893 W 563 W		689 W 558 W 355 W		824 W 670 W 430 W		981 W 794 W 505 W		1188 W 957 W 603 W		736 W 597 W 380 W		887 W 722 W 463 W		1053 W 853 W 534 W		1269 W 1022 W 634 W		300
853 W 691 W 439 W		1013 W 824 W 529 W		1224 W 990 W 629 W		1476 W 1190 W 750 W		919 W 745 W 474 W		1099 W 894 W 574 W		1308 W 1059 W 673 W		1584 W 1277 W 804 W		982 W 796 W 507 W		1183 W 962 W 618 W		1404 W 1137 W 724 W		1692 W 1363 W 858 W		400
1067 W 863 W 549 W		1266 W 1030 W 661 W		1530 W 1238 W 786 W		1845 W 1488 W 938 W		1149 W 931 W 592 W		1374 W 1117 W 717 W		1635 W 1323 W 841 W		1980 W 1596 W 1005 W		1227 W 994 W 634 W		1479 W 1203 W 772 W		1755 W 1421 W 905 W		2115 W 1704 W 1072 W		500
1280 W 1036 W 658 W		1519 W 1236 W 794 W		1836 W 1485 W 943 W		2214 W 1785 W 1125 W		1379 W 1117 W 711 W		1649 W 1341 W 861 W		1962 W 1588 W 1010 W		2376 W 1915 W 1206 W		1472 W 1193 W 761 W		1775 W 1443 W 926 W		2106 W 1706 W 1086 W		2538 W 2045 W 1286 W		600
1493 W 1209 W 768 W		1772 W 1442 W 926 W		2142 W 1733 W 1110 W		2583 W 2083 W 1313 W		1609 W 1303 W 829 W		1924 W 1564 W 1004 W		2289 W 1853 W 1178 W		2772 W 2234 W 1407 W		1718 W 1392 W 887 W		2071 W 1684 W 1081 W		2457 W 1990 W 1267 W		2961 W 2385 W 1501 W		700

Suggested retail prices in Euro exclude Vat.

All quoted prices refer to standard colour white (RAL9016)

☐ - The radiators are available on request with an eight-week delivery time.